

Hardmount Washer-Extractors

			SCT020	SCT030	SCT040
Control Option			Quantum Touch/Gold	Quantum Touch/Gold	Quantum Touch/Gold
Capacity - lb (kg)			20 (9)	30 (13.6)	40 (18)
Overall Width - in (mm)			26 (660)	29 (737)	30.6 (777)
*Overall Depth - in (mm)			30.9 (785)	35.3 (897)	42.3 (1074)
Overall Height - in (mm)			43 (1092)	45 (1143)	47.2 (1199)
Cylinder Diameter - in (mm)			21 (533)	24 (610)	26.3 (668)
Cylinder Depth - in (mm)			13.8 (351)	16 (406)	20.3 (516)
Cylinder Volume - cu. ft (liters)			2.8 (79)	4.2 (119)	6.3 (178)
Door Opening Size - in (mm)			11.6 (295)	14.3 (363)	16.3 (414)
Door Bottom to Floor - in (mm)			14.4 (366)	14 (356)	14.6 (371)
Water Inlet Connection - in (mm)			2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)
Drain Diameter - in (mm)			1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Height to Floor - in (mm)			3.9 (99)	4.3 (109)	4.5 (114)
Motor Power Consumption - HP (kW)			1 (0.75)	1 (0.75)	2 (1.5)
Total # of Speeds			9	9	9
Cylinder Speeds - RPM (G-Force)	Gentle		37 (0.4)	34 (0.4)	33 (0.4)
	Wash		51 (0.8)	48 (0.8)	46 (0.8)
	Distribution		92 (2.5)	86 (2.5)	82 (2.5)
	Very Low		301 (27)	282 (27)	269 (27)
	Low		518 (80)	485 (80)	464 (80)
	Medium		579 (100)	542 (100)	518 (100)
	High		648 (125)	606 (125)	579 (125)
	Very High		710 (150)	664 (150)	635 (150)
	Ultra High		819 (200)	766 (200)	733 (200)
** Voltage/Circuit Breaker - FLA	B	120/60/1	15-9	15-12	20-15
	X	200-240/50-60/1/3	15-4 (1 Ph) 15-3 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-4 (3 Ph)
Shipping Dimensions Approx.- in (mm)	Width		28 (711)	31.5 (800)	32.5 (826)
	Depth		33.8 (859)	38.3 (973)	43.5 (1105)
	Height		49.4 (1255)	51.3 (1303)	53.6 (1361)
Net Weight - lb (kg)			340 (154)	435 (197)	550 (249)
Shipping Weight - lb (kg)			380 (172)	475 (215)	590 (268)
Slat Crate Shipping Weight - lb (kg)			460 (209)	580 (263)	680 (308)
***Agency Approvals			cUL _{us}	cUL _{us}	cUL _{us}

Hardmount Washer-Extractors

			SCT060	SCT080	SCT100
Control Option			Quantum Touch/Gold	Quantum Touch/Gold	Quantum Touch/Gold
Capacity - lb (kg)			60 (27)	80 (36)	100 (45)
Overall Width - in (mm)			34.1 (866)	41.5 (1054)	41.5 (1054)
*Overall Depth - in (mm)			44.7 (1135)	47.1 (1196)	51.1 (1298)
Overall Height - in (mm)			49.9 (1267)	57.2 (1453)	57.2 (1453)
Cylinder Diameter - in (mm)			30 (762)	36 (914)	36 (914)
Cylinder Depth - in (mm)			22 (559)	21.9 (556)	25.9 (658)
Cylinder Volume - cu. ft (liters)			9.0 (255)	12.9 (365)	15.2 (430)
Door Opening Size - in (mm)			16.3 (414)	18.5 (470)	18.5 (470)
Door Bottom to Floor - in (mm)			14.9 (378)	17.9 (455)	17.9 (455)
Water Inlet Connection - in (mm)			4 x 0.75 (19)	4 x 0.75 (19)	4 x 0.75 (19)
Drain Diameter - in (mm)			1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Height to Floor - in (mm)			4.9 (124)	5.1 (130)	5.1 (130)
Motor Power Consumption - HP (kW)			3 (2.2)	5 (3.7)	5 (3.7)
Total # of Speeds			9	9	9
Cylinder Speeds - RPM (G-Force)	Gentle		31 (0.4)	28 (0.4)	28 (0.4)
	Wash		43 (0.8)	39 (0.8)	39 (0.8)
	Distribution		77 (2.5)	70 (2.5)	70 (2.5)
	Very Low		252 (27)	230 (27)	230 (27)
	Low		434 (80)	396 (80)	396 (80)
	Medium		485 (100)	443 (100)	443 (100)
	High		542 (125)	495 (125)	495 (125)
	Very High		594 (150)	542 (150)	542 (150)
	Ultra High		686 (200)	626 (200)	568 (165)
** Voltage/Circuit Breaker - FLA	B	120/60/1	-	-	-
	X	200-240/50-60/1/3	15-11 (1 Ph) 15-7 (3 Ph)	20-15 (1 Ph) 15-9 (3 Ph)	20-16 (1 Ph) 15-10 (3 Ph)
Shipping Dimensions Approx.- in (mm)	Width		37.5 (953)	44 (1118)	44 (1118)
	Depth		46.9 (1191)	54.5 (1384)	58.5 (1486)
	Height		56.3 (1430)	59.6 (1514)	59.6 (1514)
Net Weight - lb (kg)			680 (308)	1250 (567)	1280 (581)
Shipping Weight - lb (kg)			720 (327)	1300 (590)	1330 (603)
Slat Crate Shipping Weight - lb (kg)			840 (381)	1430 (649)	1460 (662)
***Agency Approvals			cUL _{us}	cUL _{us}	cUL _{us}

*Overall depth includes vacuum breaker to door handle.

**Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

*** Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.P.

For the most accurate information, the installation guide should be used for all design and construction purposes.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.