

Stacked Washer-Extractor/Tumble Dryers

			SST30		SST50	
			Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option			Quantum Touch		Quantum Touch	
Capacity - lb (kg)			30 (13) x 2		50 (23) x 2	
Overall Width - in (mm)			31.4 (797)		34.4 (875)	
Overall Depth - in (mm)			45.5 (1152)		51.3 (1302)	
Overall Height - in (mm)			79.7 (2023)		84.3 (2141)	
Cylinder Diameter - in (mm)			24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)			16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume - cu. ft (liters)			4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder			-	Standard	-	Standard
Door Opening Size - in (mm)			14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)			14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)			2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter - in (mm)			1 x 3 (76)	-	1 x 3 (76)	-
Drain Height to Floor - in (mm)			4.3 (108)	-	4.5 (115)	-
Heat Input Power - Btu/hr (kW, Mj/hr.)			-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection - in			-	1/2 NPT	-	1/2 NPT
Air Outlet - in (mm)			-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow - cfm (l/sec)			-	400 (190)	-	600 (285)
Motor - HP (kW)	Fan		-	0.5 (0.4)	-	0.5 (0.4)
	Drive		1 (0.75)	0.3 (0.2)	2 (1.5)	0.5 (0.4)
Total # of Speeds			9	-	9	-
Cylinder Speeds - RPM (G-Force)	Gentle		34 (0.4)	-	33 (0.4)	-
	Wash		48 (0.8)	-	46 (0.8)	-
	Distribution		86 (2.5)	-	82 (2.5)	-
	Very Low		282 (27)	-	269 (27)	-
	Low		485 (80)	-	464 (80)	-
	Medium		542 (100)	-	518 (100)	-
	High		606 (125)	-	579 (125)	-
	Very High		664 (150)	-	635 (150)	-
	Ultra High		766 (200)	-	733 (200)	-
Electrical Specs - amps	X	200-240V/50/60/1/3	15	10	15	10
Shipping Dimensions Approx. - in (mm)	Width		34.5 (876)		35.5 (902)	
	Depth		47.0 (1194)		54.0 (1372)	
	Height		83.0 (2108)		89.0 (2261)	
Net Weight - lb (kg)			770 (349)		910 (413)	
Shipping Weight - lb (kg)			787 (357)		930 (422)	
Agency Approvals			UL _{US}	CSA	UL _{US}	CSA

For the most accurate information, the installation guide should be used for all design and construction purposes.
 Due to continuous product improvements, design and specifications subject to change without notice.
 The quality management systems of Alliance Laundry Systems are registered to ISO 9001.