



The Proven Performer in Laundry

SPEED QUEEN® ON-PREMISES LAUNDRY SOLUTIONS

Stacked Washer-Extractor/Tumble Dryer

SST50

2×50 lb (25 kg)

Maximize Time and Space

Speed Queen's stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.

- Ideal for small OPL settings with limited space
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options

3 Year
Warranty

See Speed Queen Warranty Bond for specifics.



Stacked Washer-Extractor/Tumble Dryer

			SST50	
			Washer-Extractor	Tumble Dryer
Control Option			OPL Touch	
Capacity - lb (kg)			50 (25) x 2	
Overall Width - in (mm)			34.4 (875)	
Overall Depth - in (mm)			51.3 (1302)	
Overall Height - in (mm)			84.3 (2141)	
Cylinder Diameter - in (mm)			26.3 (668)	33.0 (838)
Cylinder Depth - in (mm)			20.3 (515)	30.0 (762)
Cylinder Volume - cu. ft (liters)			6.3 (178)	14.8 (419)
Reversing Cylinder			–	Standard
Door Opening Size - in (mm)			16.3 (414)	26.9 (683)
Door Bottom to Floor - in (mm)			14.6 (370)	52.3 (1328)
Water Inlet Connection - in (mm)			2 x 0.75 (19)	–
Drain Diameter - in (mm)			1 x 3 (76)	–
Drain Height to Floor - in (mm)			4.5 (115)	–
Heat Input Power - Btu/hr (kW, Mj/hr.)			–	95,000 (27.8, 100)
Gas Connection - in			–	1/2 NPT
Air Outlet - in (mm)			–	10.0 (250) Elliptical
Airflow - cfm (l/sec)			–	600 (285)
Motor - HP (kW)	Fan		–	0.5 (0.4)
	Drive		2 (1.5)	0.5 (0.4)
Total # of Speeds			6	–
Cylinder Speeds - RPM (G-Force)	Gentle		33 (0.4)	–
	Wash		46 (0.8)	–
	Distribution		82 (2.5)	–
	Very Low		269 (27)	–
	Low		464 (80)	–
	Medium		518 (100)	–
	High Extract		579 (125)	–
	Very High Extract		635 (150)	–
Ultra High Extract			733 (200)	–
Electrical Specs - amps	X	200-240V/50/60/1/3	15	10
Shipping Dimensions Approx. - in (mm)	Width		35.5 (902)	
	Depth		54.0 (1372)	
	Height		89.0 (2261)	
Net Weight - lb (kg)			910 (413)	
Shipping Weight - lb (kg)			930 (422)	
Agency Approvals			cUL _{us}	CSA

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.